SENSORS AND ACTUATORS A VOLUME 43, NUMBERS 1–3, MAY 1994

Contents

Preface 1
A. Sasaki (Kyoto, Japan)

General

Design optimisation of integrated microhotplates 3
N.R. Swart and A. Nathan (Waterloo, Ont., Canada)

Physical Sensors

Fabrication of a magnetic transducer composed of a high-density array of microelectromagnets with on-chip electronics 11
F. Cardot, J. Gobet, M. Bogdanski and F. Rudolf (Neuchâtel, Switzerland)

Surface micromachined tuneable interferometer array 17
K. Aratani (Tokyo, Japan), P.J. French, P.M. Sarro (Delft, Netherlands), D. Poenar (Tokyo, Japan), R.F. Wolffenbuttel and S. Middelhoek (Delft, Netherlands)

Liquid and gas micro-calorimeters for (bio)chemical measurements 24
A.W. van Herwaarden, P.M. Sarro (Delft, Netherlands), J.W. Gardner (Coventry, UK) and P. Bataillard (Basle, Switzerland)

A CMOS-compatible monolithic conductivity sensor with integrated electrodes 31
N. Kordas, Y. Manoli, W. Mokwa and M. Rospert (Duisburg, Germany)

A Love wave sensor for (bio)chemical sensing in liquids 38
G. Kovacs, M.J. Vellekoop, R. Haueis, G.W. Lubking and A. Venema (Delft, Netherlands)

Control of the dynamic range and sensitivity of a surface plasmon resonance based fiber optic sensor 44
R.C. Jorgenson and S.S. Yee (Seattle, WA, USA)

An optical sensor for the non-invasive measurement of the blood oxygen saturation of an artificial heart according to the variation of hematocrit 49
K. Kwon and S. Park (Taegu, South Korea)

A system for passive implantable pressure sensors 55
L. Rosengren, P. Rangsten, Y. Bäcklund, B. Hök, B. Svedbergh and G. Selén (Uppsala, Sweden)

High temperature pressure sensor using double SOI structures with two Al_2O_3 films 59
Y.-T. Lee, H. Seo, M. Ishida, S. Kawahito and T. Nakamura (Toyohashi, Japan)

Micromachined gyroscopes 65
J. Söderkvist (Täby, Sweden)

A study of silicon angular rate sensors using anisotropic etching technology 72
K. Maenaka (Hyogo, Japan) and T. Shiozawa (Nagano, Japan)

Light-to-light transducer with detection of brightness difference 78
S. Noda, K. Shibata and A. Sasaki (Kyoto, Japan)

Optical system for pressure and temperature sensing 85
K. Seibert, D. Largeau, B. Bonvalot (Montrouge, France), D.T. Angelidis and P. Parsons (Farnborough, UK)

Fabrication and packaging of a resonant infrared sensor integrated in silicon 92
C. Cabuz (Bucharest, Romania), S. Shoji, K. Fukatsu (Sendai, Japan), E. Cabuz (Bucharest, Romania), K. Minami and M. Esashi (Sendai, Japan)

Application of electrostatic feedback to critical damping of an integrated silicon capacitive accelerometer 100
R.P. van Kampen, M.J. Vellekoop, P.M. Sarro and R.F. Wolffenbuttel (Delft, Netherlands)

A miniature high-sensitivity broad-band accelerometer based on electron tunneling transducers 107
H.K. Rockstad, T.W. Kenny, J.K. Reynolds, W.J. Kaiser (Pasadena, CA, USA) and T.B. Gabrielson (Warminster, PA, USA)

Elsevier Science S.A.

Fabrication and characterization of a twin-mass accelerometer 115
C. Burrer, J. Esteve, J.A. Plaza, M. Bao (Bellaterra, Barcelona, Spain), O. Ruiz and J. Samitier (Barcelona, Spain)

A novel degree of freedom separation technique in a multi-axis accelerometer 120
K. Yamada and T. Kuriyama (Kanagawa, Japan)

A fluxgate magnetic sensor with micro-solenoids and electroplated permalloy cores 128
S. Kawahito, Y. Sasaki, H. Sato, T. Nakamura and Y. Tadokoro (Toyohashi, Japan)

High sensitivity Hall sensors with low thermal drift using AlGaAs/InGaAs/GaAs heterostructures 135
V. Mosser (Montrouge, France), S. Contreras (Montpellier, France), S. Aboulhouda (Montrouge, France), Ph. Lorenzini, F. Kobbi, J.L. Robert (Montpellier, France) and K. Zekentes (Heraklion, Crete, Greece)

Detection of actomyosin depolymerization by piezoelectric quartz crystal: possibility for development of a meat-freshness sensor 141
S. Kurosawa (Sapporo, Japan), E. Nemoto (Katsuta, Japan), M. Muratsugu, H. Ikeda (Asahikawa, Japan), M. Yoshimoto, Y. Mori, H. Kitajima and N. Kamo (Sapporo, Japan)

On a sensor to detect the point just before the dozing off state is reached 145
M. Fujikake Funada (Tochigi, Japan), Y. Yazu, H. Ide (Tokyo, Japan), K. Idogawa (Chiba, Japan), F. Yano (Tokyo, Japan), N. Daimon (Kanagawa, Japan) and S.P. Ninomija (Tokyo, Japan)

Light-emitting diodes in porous silicon 153
F. Kozlowski, P. Steiner, W. Lang and H. Sandmaier (Munich, Germany)

Surface micromachined pressure sensors with integrated CMOS read-out electronics 157
H. Dudaicevs, M. Kandler, Y. Manoli, W. Mokwa and E. Spiegel (Duisburg, Germany)

Spectral response of a photodiode using 3C-SiC single crystalline film 164
Y. Hirabayashi, S. Karasawa, K. Kobayashi (Yokohama, Japan), S. Misawa and S. Yoshida (Ibaraki, Japan)

Mechanical light modulator fabricated on a silicon chip using SIMOX technology 170
W.R. Wiszniewski (Homebush, NSW, Australia), R.E. Collins and B.A. Pailthorpe (Sydney, NSW, Australia)

Evaluation of liquid properties using a silicon Lamb wave sensor 175
M.J. Vellekoop, G.W. Lubking, P.M. Sarro and A. Venema (Delft, Netherlands)

A piezoresistive humidity sensor 181
G. Gerlach and K. Sager (Dresden, Germany)

A thin film bolometer using porous silicon technology 185
W. Lang, P. Steiner, U. Schaber and A. Richter (Munich, Germany)

A silicon VLSI optical sensor for pattern recognition 188
W.O. Camp (Owego, NY, USA) and J. Van der Spiegel (Philadelphia, PA, USA)

A micromachined pressure sensor with fiber-optic interferometric readout 196
M.A. Chan, S.D. Collins and R.L. Smith (Davis, CA, USA)

Microfabricated surface plasmon sensing system 202
R. Garabedian, C. Gonzalez, J. Richards, A. Knoesen, R. Spencer, S.D. Collins and R.L. Smith (Davis, CA, USA)

AT-cut quartz resonators for determination of viscoelastic and dielectric properties of water/glycerol 208
H.-T. Sun, L.-Y. Zhang, X. Yao (Xi'an, China) and W. Wlodarski (Melbourne, Vic., Australia)

A technique for measuring strain in layered structure media 213
K. Toda (Yokosuka, Japan), G. Sugizaki, T. Takenaka and K. Sakata (Chiba, Japan)

Enhanced mode detection for microwaves using a high-impedance YBCO–BiO composite superconductor 217
K. Niki, M. Kamino, K. Shimaoka, Y. Yoshisato, T. Ikemachi and S. Nakano (Osaka, Japan)

Materials and Technology

Low-temperature silicon wafer-to-wafer bonding using gold at eutectic temperature 223
R.F. Wolffenbuttel (Delft, Netherlands) and K.D. Wise (Ann Arbor, MI, USA)

Stiction of surface micromachined structures after rinsing and drying: model and investigation of adhesion mechanisms 230
R. Legtenberg, H.A.C. Tilmans, J. Elders and M. Elwenspoek (Enschede, Netherlands)

Application of porous silicon as a sacrificial layer 239
W. Lang, P. Steiner, A. Richter, K. Marusczyk (Munich, Germany), G. Weimann (Garching/Munich, Germany) and H. Sandmaier (Munich, Germany)

Vacuum packaging for microsensors by glass–silicon anodic bonding 243
H. Henmi, S. Shoji, Y. Shoji, K. Yoshimi and M. Esashi (Sendai, Japan)

Buried piezoresistive sensors by means of MeV ion implantation 249
T. Nishimoto, S. Shoji and M. Esashi (Sendai, Japan)

Study on fine patterning processes with a thick resist 254
K. Suzuki (Ibaraki, Japan)

SiC for sensors and high-temperature electronics 259
G. Müller, G. Krötz (Munich, Germany) and E. Niemann (Frankfurt, Germany)

Mechanical and optical properties of surface micromachined torsional mirrors in silicon, polysilicon and aluminum 269
V.P. Jaecklin, C. Linder, J. Brugger, N.F. de Rooij, J.-M. Moret and R. Vuilleumier (Neuchâtel, Switzerland)

Interface Electronics and Sensor Systems

Developments in integrated smart sensors 276
J.H. Huijsing, F.R. Riedijk and G. van der Horn (Delft, Netherlands)

Fabrication of CMOS IC for telemetering biological signals from multiple subjects 289
J. Park, S. Choi (Kyungsan City, South Korea), H. Seo and T. Nakamura (Toyohashi, Japan)

A monolithic sensor array of individually addressable microelectrodes 296
R. Kakerow, Y. Manoli, W. Mokwa, M. Rospert (Duisburg, Germany), H. Meyer, H. Drewer, J. Krause and K. Cammann (Münster, Germany)

Micromechanics

Piezoelectric force sensor for scanning force microscopy 305
T. Itoh and T. Suga (Tokyo, Japan)

Continuous ink-jet print head utilizing silicon micromachined nozzles 311
L. Smith, A. Söderbärg (Uppsala, Sweden) and U. Björkengren (Lund, Sweden)

Accurate microscopic method to investigate the aging of micromachined silicon actuators 317
R.A. Buser (Zurich, Switzerland) and A. Dommann (Buchs, Switzerland)

Characterization of an inchworm prototype motor 322
M. Bexell, A.-L. Tiensuu, J.-Å. Schweitz, J. Söderkvist and S. Johansson (Uppsala, Sweden)

Bistable fluidic elements in LIGA technique for flow control in fluidic microactuators 330
J. Vollmer, H. Hein, W. Menz and F. Walter (Karlsruhe, Germany)

Integrated flow-regulated silicon micropump 335
V. Gass, B.H. van der Schoot, S. Jeanneret and N.F. de Rooij (Neuchâtel, Switzerland)

Microlever with combined integrated sensor/actuator functions for scanning force microscopy 339
J. Brugger, N. Blanc, Ph. Renaud and N.F. de Rooij (Neuchâtel, Switzerland)

Design and fabrication of an overhanging *xy*-microactuator with integrated tip for scanning surface profiling 346
P.-F. Indermuehle, C. Linder, J. Brugger, V.P. Jaecklin and N.F. de Rooij (Neuchâtel, Switzerland)

Integrated shielding lines on multilayer polysilicon resonators 351
M.-A. Grétillat, C. Linder and N.F. de Rooij (Neuchâtel, Switzerland)

Development of piezoelectric micromovement actuator fabrication using a thick-film double-paste printing method 357
H. Moilanen, J. Lappalainen and S. Leppävuori (Oulu, Finland)

Microrobot actuated by a vibration energy field 366
T. Yasuda, I. Shimoyama and H. Miura (Tokyo, Japan)

Electrodeposited electrostatic rigid-rotor wobble motors on silicon 371
L. Paratte and N.F. de Rooij (Neuchâtel, Switzerland)

Conference Calendar 378
Author Index of Volume 43 380
Subject Index of Volume 43 381

The publisher encourages the submission of articles in electronic form thus saving time and avoiding rekeying errors. A leaflet describing our requirements is available from the publisher upon request.